



# Product Sheet

# Define 7 XL



# Index

<b>3</b>	<b>Overview</b>
<b>4</b>	<b>Key features</b>
<b>5-6</b>	<b>General specifications</b>
<b>7</b>	<b>Package contents</b>
	<b>Additional information</b>

# Define 7 XL

## Re-defining capacity.

The Define 7 XL sets a new standard for what you should expect from a full tower case in terms of modularity, flexibility and ease of use.

With its dual-layout interior, industrial sound damping and massively versatile layout supporting the largest E-ATX and enterprise boards, multi-GPU setups, outlandish water loops, and almost two dozen storage devices (in Storage layout), you'll be hard pressed to find a limit to what you can do with your build in the Define 7 XL.



# Key features

- Spacious, extensively adaptable dual-layout interior easily accommodates large motherboards up to E-ATX and SSI-EEB
- Mount up to 18 HDD/SSDs plus five SSDs in the Storage Layout (6 HDD/SSD trays + 2 SSD brackets + 2 multi-brackets included)
- Use the Open Layout for more headroom and gargantuan water-cooling with radiators up to 480 mm in front or top and 280 mm in the base
- Two 5.25" ODD bays can be converted to an additional front fan mount with filtered louver covering
- Silence-optimized construction with industrial sound-damped front, top, and side panels
- Top panel effortlessly swaps from sound damped solid steel to filtered ventilation
- New chassis design opens up to fully expose the case interior on three sides for totally unhindered installation and cable routing
- Anodized aluminum front panel with reversible dual-handed hinges opens and closes easily with magnetic latching
- Outstanding cooling capacity with a total of 9 x 140 mm or 11 x 120 mm fan mounts and three preinstalled Dynamic X2 GP-14 fans
- Versatile new multi-brackets convert any unused fan position to an HDD, SSD or pump mount
- Three vertical GPU slots for use with the Flex VRC-25 PCIe riser, available separately
- Five front USB ports including one USB 3.1 Gen 2 Type-C with fast charging support and speeds up to 10Gbps
- Ultra-slim Nexus+ 2 fan hub connects up to three PWM fans and six 3-pin fans directly in line with cable channels along the edge of the case
- Sturdy new HDD cage design with vibration damped trays
- Tool-less, top-latching panels allow quick access while preventing accidental drops
- Bridgeless expansion slots ensure obstruction-free connections for easier installation and hookup
- Ventilated PSU shroud with two-part removable cover
- Easy-to-clean high airflow nylon filters on the front, top, and base with full PSU coverage and convenient front access
- 13 pass-through holes with ten rubber grommets and two removable covers make for clean cable routing regardless of motherboard size
- Detachable PSU cable shield and integrated cable guides with Velcro straps further simplify cable management behind the board

# General specifications

3.5"/2.5" drive mounts	• 6 + 2 included, 18 positions total
Dedicated 2.5" drive mounts	• 2 included, 5 positions total
5.25" drive mounts	• 2
Expansion slots	• 9 + 3
Motherboard compatibility	• E-ATX / ATX / mATX / mITX / EE-ATX / SSI-CEB / SSI-EEB
Power supply type	• ATX
Front interface	• 1 x USB 3.1 Gen 2 Type-C, 2 x USB 3.0, 2 x USB 2.0, Audio I/O, Power button, Reset button
Total fan mounts	• 11 x 120 mm or 9 x 140 mm
Front fan	• 4 x 120 mm or 3 x 140 mm, (2 x Dynamic X2 GP-14 included)
Top fan	• 4 x 120 mm or 3 x 140 mm
Rear fan	• 1 x 120/140 mm, (1 x Dynamic X2 GP-14 included)
Bottom fan	• 2 x 120/140 mm
Dust filters	• Top, 2 x Front, Bottom + PSU
Front radiator	• Up to 480/420 mm
Top radiator	• Up to 480/420 mm
Rear radiator	• 120 mm
Bottom radiator	• Up to 240/280 mm
PSU max length	• 250 mm (both HDD cages installed)
GPU max length	• Storage layout: 359 mm • Open layout: 549 mm (524 mm w/ front fan)

# General specifications

CPU cooler max height	• 185 mm
Cable routing space	• 30 mm
Cable routing grommets	• Yes
Fixed Velcro straps	• Yes
Tool-less push-to-lock	• Both side panels and top
Captive thumbscrews	• HDD brackets, SSD brackets, PSU bracket
Left side panel	• Industrial sound-damped steel or Tempered glass
Right side panel	• Industrial sound-damped steel
Case dimensions (LxWxH)	• 604 x 240 x 566 mm
Case dimensions w/o feet/protrusions/screws	• 590 x 240 x 548 mm
Net weight	• TG: 16.64 kg • Solid: 16.53 kg
Package dimensions (LxWxH)	• 646 x 357 x 708 mm
Gross weight	• TG: 18.84 kg • Solid: 18.73 kg

# Package contents

- Define 7 XL
- Accessory box
- User manual
- Ventilated top panel
- ODD bracket
- ODD bay cover
- 2 x HDD/SSD trays

# Additional information

Product	SKU	EAN	UPC	JAN
Define 7 XL Black Solid	FD-C-DEF7X-01	7340172702047	843276102043	4537694274296
Define 7 XL Black TG Light Tint	FD-C-DEF7X-02	7340172702054	843276102050	4537694274302
Define 7 XL Black TG Dark Tint	FD-C-DEF7X-03	7340172702061	843276102067	4537694275385