

- \* Includes Intel 80486DX2 running at 50 MHz.
  - \* VESA local bus (VL-Bus) S3 GUI accelerator provides superior Windows and VGA performance.
  - \* ZIF (Zero-Insertion-Force) socket allows easy Intel Pentium performance upgrades.
  - \* 1 MB Video RAM standard, expandable to 2 MB.
  - \* 4 MB System RAM standard, expandable to 64 MB.
  - \* 8K CPU cache, expandable on-board to 1 MB write-back, direct mapped.
  - \* "Fast" IDE hard drive interface with block mode support.
  - \* 1.44 MB Floppy drive, with 2.88 MB FD support.
  - \* Industry-standard keyboard with PS/2-style mouse.
  - \* Ports:
    - 1 PS/2 keyboard
    - 1 PS/2 mouse
    - 1 parallel printer
    - 2 DB9 serial
  - \* ISA Expansion slots:
    - 4 full-length
    - 3 half-length
  - \* Case-mounted speaker.
  - \* 3 5.25" drive bays accessible.
  - \* 1 3.5" FD drive bay.
  - \* 1 3.5" internal HD drive bay.
  - \* 200-Watt power supply.
  - \* 18.2 x 6.5 x 17.4" (H x W x D)
  - \* 34 pounds.
  - \* MS-DOS, OS/2, and Novell certified.
  - \* Software included:
    - MS-DOS 6
    - America Online
    - Microsoft Windows 3.1
    - Microsoft Works for Windows 2.0
- > only with system that have hard drives installed.

