

## AUDIO-IN PIN ASSIGNMENTS

PC SPEAKER CONNECTOR (JP1)		
PIN	SIGNAL	I/O
1	+5 V	IN
2	SPK	IN

PC SPEAKER CONNECTOR (JP1)		
PIN	SIGNAL	I/O
1	Ground	
2	CD Left Channel	
3	Ground	
4	CD Right Channel	

## AUDIO EXTENSION PIN ASSIGNMENTS

CONNECTOR JP2		
PIN		
1	MICR	Mic input: Right channel. Input ranges from 0.004 to 0.7 V ms.
2	MICGEN	Mic input: Ground
3	MICL	Mic input: Left channel. Input ranges from 0.004 to 0.7 V ms.
4	SPKGND	Speaker output: Ground.
5	SPKR	Speaker output: Right channel. Maximum output voltage is 3 V ms at 4 ohms.
6	SPKL	Speaker output: Left channel. Maximum output voltage is 3 V ms at 4 ohms.
7	SPKRL	Speaker output return signal: Left channel.
8	SPKRR	Speaker output return signal: Right channel.

|-----|

CONNECTOR JP2		
PIN		
1	SPKR	Speaker output: Right channel. Maximum output voltage is 3 V ms at 4 ohms.
2	SPKRR	Speaker output return signal: Right channel.

(smm 08/02/93)